



LINELIGHT HELLIFLEX MIDI

FUNCTION DESCRIPTION

Flexible LED strip with an operation voltage of 24 V-DC, available in LED RGB, RGBW or warm white. The strip can be either installed with holding brackets (e.g. if installed in wooden cabinets) or with a mounting profile (e.g. if installed under the benches of steam rooms). The Helliflex system is prepared with a double-sided adhesive tape on the backside and available in different standard lengths. The lengths is adaptable on site. Therefore, a protection cap made of transparent silicon is included in the scope of delivery.



SCOPE OF DELIVERY

- LED light strip, casted in 2-components resin with 4 m cable and AMP plug
- Protection cap for adaption of the length on site

TECHNICAL DATA

	RGB	RGBW	Warm White
Control signal	24 V-DC RGB - / com +	24 V-DC RGB - / com +	24 V-DC
Light colour	Red/Green/Blue	Red/Green/Blue/Warm White	Warm White 2700 K
Dimensions (W/H/L)	13 x 5 mm x length	15 x 5 mm x length	11 x 5 mm x length
Temperature range		-20 to +60 °C	
Protection class		IP68	

ACCESSORIES / OPTIONS

- Recommendation:
Aluminium installation profile 17 x 5 mm - available in pieces of 2 or 3 m
- Holding brackets for Helliflex-Midi